

05/09/05 MON 15:05 FAX 308 2571

TC 3600

REC'D VIA FAX
MAY 10 2005

1/5

UNITED STATES PATENT AND TRADEMARK OFFICE
Jeffrey Sharpman Kanesaka BernerCommissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.govRECEIVED
CENTRAL FAX CENTER

MAY 12 2005

Fax Cover Sheet

Date: 09 May 2005

To: Manabu Kanesaka

From: Jeffrey Sharp

Application/Control Number: 10/650,722

Art Unit: 3677

b - 1490

Fax No.: (703) 519-7769

Phone No.: (571) 272-7074

Voice No.: 703-519-9785

Return Fax No.: (703) 872-9308

Re: After Final Amendment

CC:

☒ Urgent☒ For Review☒ For Comment☒ For Reply☐ Per Your Request

Applicant agreed your proposal.

Please add "of" after "surface" in claim 1, line 13.

Thank you.

Manabu Kanesaka

5/12/05

3/5

Proposed Amendment to the claims (After final 10/650,722)

1. (currently amended) A connector for fastening a member with an attaching hole, comprising:
a female part having a head portion, a leg portion connected to the head portion, an inner space formed in the leg portion and opened at the head portion, and an engaging projection formed as a tab on an outer surface of the leg portion by a surrounding cutout portion, said engaging projection having a first strength to elastically bend inwardly to engage the attaching hole when the leg portion is inserted into the attaching hole, and a male part having a pressing head portion, an inserting leg connected to the pressing head portion to be inserted into the inner space of the female part, a first engaging portion formed on an outer surface of the inserting leg at forward end thereof for engaging an inner wall of the female part so that the male part is temporarily fixed to the female part at a temporary engaging state, ~~[[and]]~~ a second engaging portion including a projection on the outer surface ^{of} the inserting leg at a base end thereof to project outwardly therefrom, and an empty space for allowing the projection of the second engaging portion to bend elastically inwardly, said second engaging portion, when the male part is completely inserted into the female part from the temporary engaging state to a complete engaging state, being ~~[[disposed in]]~~ inwardly bent and elastically engaged with the inner wall of the female part to permanently fix the connector to the attaching hole, said second engaging portion having a second strength greater than the first strength so that when male part in the temporary engaging state with the female part is pushed to engage said member, the engaging projection with the first